



Collection:

## Technical Specifications

|                       |                           |
|-----------------------|---------------------------|
| Air Mixing Capability | Yes                       |
| Badge Diameter (mm)   | D50                       |
| Body Material         | Brass                     |
| Built-in Product      | 0                         |
| Cartridge             | Adjustable heat-flow rate |
| Check Valve           | VALUE: -                  |
| Colour                |                           |
| Designer              | VALUE: VitrA Design Team  |
| Easy Assembly Feature | Yes                       |
| Hose Length           | 500                       |
| Hose Material         | Stainless Steel EPDM      |
| Installation Type     | Countertop                |

|                             |                                |
|-----------------------------|--------------------------------|
| Material                    | VALUE: Matte Black             |
| Noise Class                 | I                              |
| Number of Functions         | 6                              |
| Number of Holes             | 1                              |
| Number of Jets              | VALUE: -                       |
| Number of Water Inlets      | Double Inlet                   |
| Operating Pressure          | Min:0.5-Max:10Recommended(1-5) |
| Outlet Height               | 90                             |
| Outlet Length               | 120                            |
| Outlet Rotation Angle       | Fixed                          |
| Packaged Dimensions (W×D×H) | 190 x 170 x 75                 |
| Perlator Type               | Short                          |
| Warranty Period (Years)     | 5                              |
| Water Efficiency Class      | Dark Green (0 < Flow Rate ≤ 6) |

### 2A Technical Drawing

