

Collection:

Technical Specifications

| | |
|-----------------------|---------------------------|
| Air Mixing Capability | Yes |
| Anti-twist Feature | Yes |
| Badge Diameter (mm) | D130 |
| Body Material | Brass |
| Built-in Product | 0 |
| Cartridge | Adjustable heat-flow rate |
| Certificates | VALUE: REACH |
| Check Valve | VALUE: - |
| Colour | |
| Designer | VALUE: VitrA Design Team |
| Hand Shower Outlet | Yes |
| Hose Length | 725-1500 |

| | |
|-----------------------------|--------------------------------|
| Hose Material | Polyester Braided EPDM/PVC |
| Installation Type | From the Floor |
| Material | VALUE: Matte Black |
| No-Calc Feature | Yes |
| Noise Class | II |
| Number of Functions | 1 |
| Number of Holes | 1 |
| Number of Jets | VALUE: - |
| Number of Water Inlets | Double Inlet |
| Operating Pressure | Min:0.5-Max:10Recommended(1-5) |
| Outlet Height | 915 |
| Outlet Length | 225 |
| Outlet Rotation Angle | Fixed |
| Packaged Dimensions (W×D×H) | 350 x 225 x 1130 |
| Perlator Type | Standard |

| | |
|-------------------------|-----------|
| Warranty Period (Years) | 5 |
| Water Efficiency Class | Red (>13) |
| Water Flow Rate (L/min) | 5,4 |

2A Technical Drawing

